

1 SB 3-45 A



: 97686705

Grundfos SB 3-45 A is a submersible pump designed for the pumping of clean water for domestic and rainwater applications. It is silent when submerged and therefore a noiseless alternative to surface-mounted pumps. The pump is built from high quality composite and stainless steel materials that are resistant to corrosion.

The SB 3-45 A is equipped with a 15 m supply cable, and the maximum installation depth is 10 m below the water level, with a liquid temperature ranging from 0 °C to 40 °C.

The SB 3-45 A is ideal for operation in a well or ground tanks, as it easily prevents solid particles from entering the pump. The maximum particle size is 1 mm.

The pump features a float switch, which promises the user a convenient experience with automatic start/stop operation of the pump and provides dry running protection.

The single-phase model is effectively protected against any accidental overload by built-in thermal protection.

The pump has built-in thermal protection, which immediately stops the pump if it overheats. Having cooled down, the pump automatically restarts when it reaches a normal temperature.

:

:

: 0 .. 40 °C

: 20 °C

:


998.2 / ³

:



Гидромаш Инжиниринг
044-502-39-31

Return valve:	: 2.83 ^{3/}
	: 30.1
	: 1
	- : ISO9906:2012 3B
	NO
	: 2800 /
	: Composite
Type of inlet connection:	: -10 .. 50 °C
	STRAINER
	: G 1"
	: 10
	: F
P1:	1.05
P2:	0.62
	: 50 Hz
	: 1 x 220-240
I start:	12 A
Cos :	0.94
	- : 13 /450
(IEC 34-5):	IP68
Length of cable:	15
	: H07RN-F 3G1
	: SCHUKO
Rated current:	4.8 A
	: 9.69
	: 10.4
	: 0.022 ³
Danish VVS No.:	391361045
Swedish RSK No.:	5850350
Finnish:	4822540
Norwegian NRF no.:	9041868
	: CE,WEEE
	: 8413702900

97686705 SB 3-45 A 50

:	
SB 3-45 A	
97686705	
EAN :	5710621504164
	262,55 €
:	
2.83 ^{3/}	
:	30.1
Head max:	45
:	4
:	1
- - :	ISO9906:2012 3B
Return valve:	NO
	2800 /
:	
:	Composite
:	
:	-10 .. 50 °C
Type of inlet connection:	STRAINER
:	G 1"
:	10
:	
:	0 .. 40 °C
:	20 °C
:	998.2 / ³
pH:	4-9
:	
:	F
P1:	1.05
P2:	0.62
:	50 Hz
:	1 x 220-240
I start:	12 A
Cos :	0.94
- - :	13 /450
(IEC 34-5):	IP68
:	
Length of cable:	15
:	H07RN-F 3G1
:	SCHUKO
Rated current:	4.8 A
:	
:	
:	9.69
:	10.4
:	0.022 ³
Danish VVS No.:	391361045
Swedish RSK No.:	5850350
Finnish:	4822540
Norwegian NRF no.:	9041868
:	CE,WEEE
:	8413702900

